



▼ Shown top to bottom: **LX-101**



## Enerpac System Components

### Hydraulic Oil

| Contents   | Model Number  | High viscosity index ensures maximum lubricity over a wide range of operation temperatures. |
|------------|---------------|---------------------------------------------------------------------------------------------|
|            |               |                                                                                             |
|            |               |                                                                                             |
|            |               |                                                                                             |
|            |               |                                                                                             |
| 1 Gallon** | <b>LX-101</b> |                                                                                             |

\*\* Hand pump oil.

### LX Hand Pump Oil

- Specially formulated for hand pumps
  - anti-sludge, anti-rust additives
- Reduced handle effort over HF blue oil
  - good low temperature performance
- Not for use in power pumps

### ▼ Oil Specifications Chart

|                             | HF Oil | LX Oil |
|-----------------------------|--------|--------|
| ISO Viscosity Grade         |        | 15     |
| API Gravity, ASTM D1298     |        | 34     |
| Viscosity, ASTM D445        |        |        |
| SUS @ 212°F                 |        | 38     |
| SUS @ 104°F                 |        | 77.5   |
| Viscosity Index, ASTM D2270 |        | 100    |
| Pour Point, °F, ASTM D97    |        | -47.5  |
| Flash Point, °F, ASTM D92   |        | 370    |
| Color                       |        | Yellow |

NOTE: SAE grades do not apply to hydraulic oil.